

HYBRID SERIES

# GEN-LB-US 13K

- 2 MPPTs with 4 strings input, Max. 21kW PV input
- Supports up to 10pcs in parallel for on/off grid
- Peak shaving function
- Auto start/stop, works with battery and PV for load support.
- AC coupling function to retrofit the existing grid-tied system
- Remote Monitoring & AI Optimization



Model	GEN-LB-US 13K
<b>Input(PV DC)</b>	
Max. PV array power (W)	21000
Max. PV input power (W)	18000
Rated PV input voltage (V)	360
Number of independent MPPT inputs	2/(2:2)
PV input voltage range (V)	100-550
MPPT voltage range (V)	120-440
Start-up voltage (V)	140
Max. PV input current per MPPT (A)	26/26
Max. PV short-circuit current input per MPPT (A)	31/31
<b>Battery</b>	
Compatible battery type	Lithium-ion/Lead-Acid
Rated battery voltage (V)	48
Battery voltage range (V)	40-60
Max. charging/discharging current (A)	208
Max. charging/discharging power (W)	10000
Force wake up battery from PV function	YES
<b>AC Input/AC Output</b>	
Rated AC voltage (V)	240 ; 208
Rated AC frequency (Hz)	50/60
Rated AC output power with PV (W)	13000@240V / 11200@208V
Rated AC output current with PV (A)	54
PF	0.99 (Adjustable from 0.8 leading to 0.8 lagging)
THDI	<3%
Max. continuous AC passthrough current (A)	90
<b>GEN</b>	
Rated GEN voltage (V)	240 ; 208
Rated GEN frequency (Hz)	50/60
Rated GEN input current (A)	62.5
Max. GEN input current (A)	80
Rated GEN input power (W)	15000
<b>UPS</b>	
Rated output power (W)	10000
Rated output voltage (V)	240 ;120/240 ; 120/208
Rated output current (A)	41.6@240V ; 48@208V
Rated output frequency (Hz)	50/60
Surge power, duration	2Pn, 0.5s
Switching time	20ms
Wave form	Sine wave
THDV	<3%
<b>Efficiency</b>	
Max. MPPT efficiency	99.9%
Max. efficiency	97.0%
Battery charge/discharge efficiency	94.5%
CEC efficiency	97.36%
<b>Protection</b>	
PV reverse polarity protection	YES
Over current/voltage protection	YES
Anti-islanding protection	YES
AC short-circuit protection	YES
Leakage current protection	YES
DC switch	YES
AC/DC surge protection	Type III
Rapid shut down	YES
Grid/AFCI/RSD monitoring	YES
Load breaker	80A
Battery breaker	250A/80V
<b>General</b>	
Dimensions (W*H*D)	566*773*285mm / 22.3*30.4*11.2 in
Weight	55kg / 121.3 lbs
Ingress protection rating	IP66/NEMA 4X
Relative humidity	0-100%
Operating environment temperature range (°C)	-25-60°C, > 45°C Derating
Storage temperature range (°C)	-25-60
Display & Communication interface	Touch color screen, RS485/Wi-Fi/CAN
Warranty	5/10 years
Cooling method	Smart Cooling
Topology	Transformer-less
Altitude	<2000m
<b>Standards &amp; Certification</b>	
UL1741SA, UL1741SB, CSA22.2, UL1741PCS CRD, CEC, FCC Part15B, IEEE1547.1.	